

## PRODUCT INFORMATION

# NAVACLEAN 842 ALKASAFE



## WATER BASED NON-CAUSTIC ALKALINE CLEANER.

### DESCRIPTION

- › Formulated specifically for tank cleaning
- › Will effectively remove a very wide range of natural oil and fat residues, alcohols, petrochemicals, and light hydrocarbons
- › An ideal cleaner between cargo changeovers
- › Highly concentrated making it ideal for direct injection or recirculation methods
- › Available in 25/200/208 liter drums
- › Can be discharged according to Marpol V and IMO MEPC.1/Circ. 590

### FEATURES & BENEFITS

- › Non-corrosive and safe on almost all tank coatings
- › Blended with emulsifiers and detergent wetting agents
- › Excellent deodorizing and sanitizing capacity
- › Approved according to IMMO MEPC.1/Circ. 590
- › Complies to Marpol V

For detailed instructions on cargo hold cleaning please contact us at NAVADAN.  
A range of support application equipment is also available.

# NAVADAN

## DIRECTION FOR USE

- › Navaclean 842 may be hand-sprayed at solution strengths between 30% and 100% for local cleaning and the removal of particularly stubborn deposits. Normally Navaclean 842 is used diluted with either fresh or sea water. The solution strength depends on the amount and types of residues to be removed and the cleaning method.
- › If cleaning is carried out by recirculation alone, solution strengths from 0.5% to 5% should be used. Fresh water is recommended if possible.

## PRODUCT CHARACTERISTICS

Appearance:	Transparent liquid
Specific gravity:	1.01
Flash Point:	None
pH-value(1% solution):	8

For risks and safety regulations, please see our Safety Data Sheet

The information and recommendations given herein are believed to be accurate and reliable. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without any warranty and liability, expressed or implied.