

# PRODUCT INFORMATION SHEET



**IMO APPROVED**

## NAVACLEAN 873 RUST & STAIN REMOVER

LIQUID ACID BASED RUST REMOVER AND METAL BRIGHTNER

### APPLICATION, FEATURES & BENEFITS

- Approved according to IMO MEPC.1/Circ. 590, February 2008
- Removal of white stains/strips on tank coating

### DESCRIPTION

On some coatings, washing with hot sea water after discharge of caustic or different lye cargoes, may result in white stains or stripes on tank surfaces.

NAVACLEAN 873 – RUST & STAIN REMOVER can be used to remove these white stains/strips.

### DIRECTIONS FOR USE/APPLICATIONS & DOSAGE RATES

Inject 0.5 litre of NAVACLEAN 873 – RUST & STAIN REMOVER for every 100 ltrs of washing water, directly into tank washing system (Butterworth system). Wash each tank for approx. 20-30 minutes (1 washing cycle). Recommended temperature of washing water is 75 - 80°C. Finally rinse each tank with fresh water.

**Caution:** Always add NAVACLEAN 873 - RUST & STAIN REMOVER to water.  
NAVACLEAN 873 - RUST & STAIN REMOVER should not be used on galvanised or tinned surfaces.

### PRODUCT CHARACTERISTICS

- **Appearance:** Clear liquid
- **Specific Gravity:** 1.2 at 20°C
- **pH value (1% solution):** 2
- **Flash Point:** None
- **Corrosive action:**
  - **Metals:** Slight action
  - **Rubber:** None

### NATURE OF SPECIAL RISKS AND SAFETY REGULATIONS

See our Material Safety Data Sheets

### PACKAGING

NAVACLEAN 873 is available in 200/208 litre drums.

The information and recommendations given herein are believed to be accurate and reliable. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without any warranty and liability, expressed or implied.